



Metal Tape Eraser

The V880 has been designed to bring efficient erasing of high energy cassettes and cartridges in a compact table top conveyorised degausser at an affordable price.

The conveyor transportation system of the V880 ensures that media is completely erased in an easy-to-use manner.

Extra security of erasure can be achieved by use of the optional belt cover, ensuring that media cannot be removed from the conveyor belt until it has passed completely through the erasure field.

The cassettes are placed onto the moving conveyor belt and carried over two degaussing coils which are orientated at 90 degrees to one another in a 'V' formation. The belt speed is fixed at 4 inches per second (50hz).

FEATURES:

- H High Energy 4000 Gauss Field**
- H Fast Reliable Conveyor System**
- H Powerful Dual "V" Configured Coils**

VERITY SYSTEMS LTD

Verity House, 2 Eastern Road
Aldershot, Hants, GU12 4TD, U.K.

Telephone: +44 (0)1252 317000
Fax: +44 (0)1252 316555
E-mail: sales@veritysystems.com

AGENT:

Specifications: V880

- Erasure: -75dB on 1500 Oe metal media
- Media: Cassettes:
Beta SP - large & small,
Digital Betacam - large & small,
D1,D2,D3 - small & medium,
MI, MII, Beta, Betacam,
U-Matic, U-Matic SP, VHS,
SVHS, Compact Cassettes,
Scotchcart, DAT, 8mm
Cartridges:
3480 & 3490E Cartridges
TK50,70,85,DLT Cartridges
- Throughput: 600 Beta SP per hour TYP (two passes)
- Operational Voltage:
220/240v 50Hz
208/220v 60Hz
- Current Rating:
12 amps typ
- Belt Width: 6" (153mm)
- Belt Speed: 50Hz 4ips
60 Hz 4.8ips
- Duty Cycle: 20 mins from cold
60% in the first hour (dependent on ambient temperature)
- Dimensions: Height 7.0" (177mm)
Width 15.6" (395mm)
Depth 40.2" (1,021mm)
- Weight: 150Lbs (68kg)

Verity Systems maintains a policy of continuous improvement and reserves the right to amend this specification without notice.

